MAZZOLENI

Plastic coated wire

SINTERBERG®

RINGS - ORBIT COILS

Uses

- Wire for fencing
- Wire for binding
- Wire for agriculture and hail protection systems
- Chain link fences for sport centers and civil use

©2026 MAZZOLENI TRAFILERIE BERGAMASCHE SPA – VIA PONTE PIETRA, 2 / BERGAMO, 24123 – ITALIA – T. +39 035 211004 – info.tb@mazzoleni.it – www.mazzoleni.it
COMPANY CERTIFIED ACCORDING TO ISO 9001:2015, ISO 14001:2015, AND ISO 50001:2018.

Technical data

STEEL - UNI EN 16120-2
C7D

DIAMETER RANGE
from 1,40 to 5,00 mm

TENSILE STRENGTH
from 380 to 900 N/mm2

OUTER COATING
extruded plastic wire
sintered plastic wire

INNER COATING - UNI EN 10244-2 T1 T2
zinc 99,995% • classe A/B/C/D
zinc 95% + aluminium 5% • classe A/B/C/D
zinc 90% + aluminium 10% • classe A/B/C/D

Packaging

RINGS

Ø range (mm)	weight (kg)
1,40-5,00	25-100

ORBIT COILS

Ø range (mm)	weight (kg)
1,40-5,00	400-800

Upon specific request, it is possible to agree on packaging, diameter and tensile strenght.

©2026 MAZZOLENI TRAFILERIE BERGAMASCHE SPA – VIA PONTE PIETRA, 2 / BERGAMO, 24123 – ITALIA – T. +39 035 211004 – info.tb@mazzoleni.it – www.mazzoleni.it
COMPANY CERTIFIED ACCORDING TO ISO 9001:2015, ISO 14001:2015, AND ISO 50001:2018.